

HUSKY – TECHNICAL DATA

DIMENSIONS AND WEIGHT

Overall vehicle length	4,065 mm (160 in)
Overall vehicle length with attachments	7,400 mm (291 in)
Overall vehicle length with attachments including NORDIC LINER	8,590 mm (338 in)
Overall height	2,770 mm (109 in)
Versions of working width	2.5/2.8/3.1 m
Shipping dimensions (length-width-height)	5,110 mm - 2,445 mm - 2,655 mm (201 in - 96 in - 104 in)
Vehicle weight with aluminum tracks and attachments (blade, tiller) from	5,565 kg (12,269 lb)
Permitted gross weight	7,500 kg (16,534 lb)

PERFORMANCE

Max. speed	24 km/h (14.9 mph)
Turning radius	0 (around its own axis)
Payload	500 kg (1,102 lb)

DRIVE

Drive pump	90 cm ³ (9 l)
Final drive	63 cm ³ (6.3 l)

INCLUDED FUNCTIONS IN STANDARD CONFIGURATION

Adjustable down pressure
Cruise Control
On-board diagnostics
Multiple driver profiles
Hydraulic track tensioning

CABIN

Left-hand drive, mechanical suspension, adjustable
Seat bench for 1,5 persons
7" color display
Steering wheel
PRINOTH Universal joystick
Tinted sunroof
Heated windows
Heated mirrors
Hydraulically tiltable cabin
Radio FM/AM, DAB, CD, MP3, WMA, Bluetooth®
iPod/iPad direct control via USB, AUX in
ROPS certified according to EN 15059

ENGINE

Model	MTU OM 934 LA
Power output (ECE)	170 kW/231 PS (170 kW/228 bhp)
Max. torque	900 Nm @ 1,200-1,600 min ⁻¹
Displacement	5.1 l
Layout	In line 4 cylinder, direct injection, Common Rail
Exhaust emission standard	Stufe IV/ Tier 4 final
Emission regulation type	SCR
Tank capacity fuel	150 l (39.6 gal)
Tank capacity AdBlue®	40 l (10.5 gal)

OPTIONS

Comfort seat
Steering levers
Air conditioning
Heated wipers
Full-LED equipment
Brushguard
Rear view camera
RESOURCE MANAGEMENT
SNOW DEPTH MEASUREMENT
Additional fuel tank (125 l)
Floating position blade
Side wings for tiller
Preparation for front hydraulics
Steel tracks, all season tracks

ELECTRICAL SYSTEM

Operating voltage	24 VDC
Starter	24 VDC
Generator	28 VDC/150 A
Battery	2 x 12 VDC/74 Ah
Starting capacity	680 A (EN)

LIGHTING

2 adjustable low-beam lights
4 directional spotlights
2 turning lights
1 search light
2 direction indicators
2 position lights
4 directional spotlights at the back

ADDITIONAL EQUIPMENT

NORDIC LINER basic (with/ without track tiller)
NORDIC LINER move (with/ without track tiller)

Subject to modifications in the course of technological advancement.

12-WAY BLADE

	STANDARD	MASTER
Open	3,250 mm (127 in)	3,650 mm (143 in)
Closed	2,720 mm (107 in)	3,000 mm (118 in)

TILLER

	V 2.3	V 2.5	V 2.8	V 3.1
Tiller without hydraulic side wings	3,255 mm (128 in)	3,530 mm (138 in)	3,700 mm (145 in)	4,060 mm (160 in)
Tiller with hydraulic side wings up	3,075 mm (121 in)	3,345 mm (131 in)	3,530 mm (139 in)	3,880 mm (152 in)
Tiller with hydraulic side wings down	4,095 mm (161 in)	4,365 mm (171 in)	4,550 mm (179 in)	4,900 mm (192 in)

